


Kernmantle Rope Lanyard

according to EN 354:2010



IKV 11 (EN 362:2004)



IKV 06 (EN 362:2004)

Product information:

Order No:	Length	Connection element	Opening gate (Carabiner)	Weight
45-IK 6 K 100 6	1,00 m	IKV 06	18 mm	0,58 kg
45-IK 6 K 150 6	1,50 m	IKV 06	18 mm	0,62 kg
45-IK 6 K 175 6	1,75 m	IKV 06	18 mm	0,64 kg
45-IK 6 K 200 6	2,00 m	IKV 06	18 mm	0,66 kg
45-IK 2 K 100 2	1,00 m	IKV 11	26 mm	0,36 kg
45-IK 2 K 150 2	1,50 m	IKV 11	26 mm	0,40 kg
45-IK 2 K 175 2	1,75 m	IKV 11	26 mm	0,42 kg
45-IK 2 K 200 2	2,00 m	IKV 11	26 mm	0,44 kg

Features:

Connecting component in a restraint system

- Kernmantle rope Ø 11 mm, made of polyester (abrasion resistant, dimensionally stable, light and weather resistant)
- Aluminum double action hook IKV 11 (EN 362:2004) on both end
- **or:**
- steel double action hook IKV 06 (EN 362:2004) on both end
- Connecting means and parts of a PSAgA collection system

Application:

Connection, Restraint of work positioning

Areas of use:

Industrial, construction and utility environments