

Adjustable Kernmantle Rope Lanyard

according to EN 358:2000



IKV 11 (EN 362:2004)



IKV 06 (EN 362:2004)

Product information:

Order No.:	Length	Connection element	Opening gate (Carabiner)	Weight
45-IK 6 K 100 A 6	1,00 m	IKV 06	18 mm	0,64 kg
45-IK 6 K 150 A 6	1,50 m	IKV 06	18 mm	0,68 kg
45-IK 6 K 175 A 6	1,75 m	IKV 06	18 mm	0,70 kg
45-IK 6 K 200 A 6	2,00 m	IKV 06	18 mm	0,72 kg
45-IK 2 K 100 A 2	1,00 m	IKV 11	26 mm	0,4 2kg
45-IK 2 K 150 A 2	1,50 m	IKV 11	26 mm	0,46 kg
45-IK 2 K 175 A 2	1,75 m	IKV 11	26 mm	0,48 kg
45-IK 2 K 200 A 2	2,00 m	IKV 11	26 mm	0,50 kg

Features:

Length-adjustable component in a workplace positioning system

- Kernmantle rope Ø 11 mm made of polyamid (abrasion resistant, dimensionally stable, light and weather resistant)
- Length-adjustable holding cable of the PSaGA
- Aluminum double action hook IKV 11 (EN 362:2004) at each end
- or:**
- Steel double action hook IKV 06 (EN 362:2004) at both end

Application:

Restraint of work positioning

Areas of use:

Industrial, construction and utility environments