



Datasheet

Adjustable Kernmantle Rope Lanyard

according to EN 358:2000



IKV 03 (EN 362:2004)



IKV 06 (EN 362:2004)



IKV 11 (EN 362:2004)

Product information:

Order No:	Length	Connection element	Opening gate (Carabiner)	Weight
45-IK 6 K 100 A 3	1,00 m	IKV 06 / IKV 03	18 mm / 60 mm	0,86 kg
45-IK 6 K 150 A 3	1,50 m	IKV 06 / IKV 03	18 mm / 60 mm	0,89 kg
45-IK 6 K 175 A 3	1,75 m	IKV 06 / IKV 03	18 mm / 60 mm	0,91 kg
45-IK 6 K 200 A 3	2,00 m	IKV 06 / IKV 03	18 mm / 60 mm	0,93 kg
45-IK 2 K 100 A 3	1,00 m	IKV 11 / IKV 03	26 mm / 60 mm	0,64 kg
45-IK 2 K 150 A 3	1,50 m	IKV 11 / IKV 03	26 mm / 60 mm	0,67 kg
45-IK 2 K 175 A 3	1,75 m	IKV 11 / IKV 03	26 mm / 60 mm	0,69 kg
45-IK 2 K 200 A 3	2,00 m	IKV 11 / IKV 03	26 mm / 60 mm	0,71 kg

Features:

Length-adjustable component in a workplace positioning system

- Kernmantle rope Ø 11 mm made of polyamid (abrasion resistant, dimensionally stable, light and weather resistant)
- Length-adjustable holding cable of the PSAgA
- Aluminum double action hook IKV 03 (EN 362:2004) at each end
- Aluminum double action hook IKV 11 (EN 362:2004) at each end
- or:**
- Steel double action hook IKV 06 (EN 362:2004) at the end

Application:

Restraint of work positioning

Areas of use:

Industrial, construction and utility environments

IKAR GmbH
Nobelstrasse 2
36041 Fulda

contact@ikar-gmbh.de

www.ikar-gmbh.de

Phone: +49 (0)661 - 22050