


## Auffanggurt IK G2 B Pad


according to EN 361:2002



D ring (steel)



Quick-release buckle (steel)



Quick-release buckle with buckle (chest), forged steel

### Product information:

| Order No.:      | Size   | Fall arrest D ring                  | D ring at the back                  | D ring | Waistbelt                           | Weight  |
|-----------------|--------|-------------------------------------|-------------------------------------|--------|-------------------------------------|---------|
| 45-IK G 2 B Pad | M - XL | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |        | <input checked="" type="checkbox"/> | 1,70 kg |

### Features & fields of application:

#### Two Point Fall Arrest Safety Harness

- 45 mm wide webbing of polyester (PES)
- 1 D-ring in the back (shoulder area) of forged steel
- 1 D-ring in the chest area (fall arrester eye) made of forged steel
- Integrated, waistbelt support for pressure reduction in case of interception
- Quick connect fastenings make the harness easy to fit and remove
- Individual size adjustment by leg and shoulder straps
- Nominal load: 136 kg
- Temperature range of application: -40°C bis +50°C
- Lifespan: approx 10 years

#### Application:

Fall restraint, rescue, climb

#### Areas of use:

Industrial construction, utility environments