



Safety Harness IK G2 B R



according EN 361:2002; EN 1497:2007



D ring (steel)



Quick release buckles (steel)



Quick-release buckle with buckle (chest), forged steel

Product information:

Order No.:	Size	Fall arrest D ring chest	D ring at the back	d ring	Waistbelt	Weight
45-IK G 2 B R	M - XL	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			1,60 kg

Features & fields of application:

Two Point Fall Arrest Safety Harness

- 45 mm wide webbing of polyester (PES)
- Rear dorsal fall arrest D ring and a front sternum fall arrest D ring
- 1 D-ring in the back (shoulder area) of forged steel
- 1 D-ring in the chest area (fall arrester eye) made of forged steel
- Quick connect fastenings make the harness easy to fit and remove
- Individual size adjustment by leg and shoulder straps
- Nominal load: 136 kg
- Temperature range of application: -40°C bis +50°C
- Lifespan: approx 10 years

* A fall arrest device with recovery mechanism (HRA) may be attached to this point when used in the vertical application providing the lifeline is attached from directly above i.e. confined space entry applications.

Application:

Fall restraint

Areas of use:

Industrial use, driving in narrow spaces, sewage engineering