


Safety Harness IK G4 DW R S


according to EN 361:2002, EN 1497:2007, EN 358:2000, EN 813:2008




D-Ring Aluminium (rear)




Aluminium climbing D-ring,
Waist belt with quick release



6 setting clamps



D ring (Aluminium) right hand



D ring (Aluminium) left hand

Product information:

Order No.:	Size	D ring at chest area	Fall protection height	D ring at the back	Stop loop	Waistbelt	Weight
45-IK G 4 DW R S	M - XL	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	3,1 kg

Features & fields of application:

Safety harness specially developed for IKAR passenger and load winches

- 45 mm wide webbing of polyester (PES)
- 1 D ring at the chest area
- D ring in the chest area can also be used as a safety eye
- 1 D-ring in the chest area (fall arrester eye) made of aluminium
- 1 D-ring 1 D-ring in the back (shoulder area) of aluminium
- 1 D ring on the waistbelt of aluminium
- Individual size adjustment by leg and shoulder straps
- integrated padded Waistbelt with 2 D rings, made of aluminium. For optimal workplace positioning
- Simple adjustment on shoulder straps, chest strap and leg loops to ensure maximum adjustment to fit an extensive size range
- 4 eyelets for tool pockets at the side
- Quick connect fastenings make the harness easy to fit and remove

Application:

Fall restraint . rescue, climb, backing, Work Positioning

Areas of use:

Industrial, construction, Working in narrow spaces, wastewater area